



### GENERAL INFORMATION

A water-based, Low-VOC, multi-purpose cleaner for use in initial and final surface prep. Removes grease, wax, silicone, adhesives, tar, tree sap, insects, dirt and sanding residue.



### 1. COMPONENTS

- 170 Aqua Clean



### 2. MIXING RATIO

- Ready to Use



### 3. POT LIFE @ 77°F (25°C)

- N/A



### 4. CLEAN UP

- To clean nozzle, invert can and spray for about three (3) seconds



### 5. ADDITIVES

- N/A



### 6. SURFACE PREPARATION

- N/A



### 7. TOPCOATS

- N/A



### 8. TECH NOTES

- 170 Aqua Clean should not be allowed to dry on the surface. If this occurs, re-apply 170 Aqua Clean using a clean cloth and wipe dry
- Useful for sensitive surfaces
- Always replace cap after use
- May be applied with spray bottle
- May be used as a "wet-sanding" lubricant



### 9. SUBSTRATES

- Sanded surfaces
- OEM finishes
- Cured sealers
- Sanded primers
- Aluminum
- Plastics



### 10. APPLICATION

- Wash surface with mild detergent and water
- Rinse and dry surface
- Soak clean cloth with 170 Aqua Clean
- Wipe surface with 170 Aqua Clean and wipe dry with clean cloth before product dries



### 11. FLASH/DRY TIMES

- N/A



### 12. INFRARED CURE

- N/A



### 13. GUN SET UP

- N/A



### 14. PHYSICAL DATA

FOR USA/Canada (0.25/0.5 LBS.GAL Actual VOC Compliance)

RTS REGULATORY DATA:	AS IS	
	170	
	LBS./GAL	g/L
Actual VOC	0.20 Max.	25 Max.
Density	7.5 - 8.5	900 - 1020
	WT.%	VOL.%
Total Solids Content	0.25 - 0.50	0.25 - 0.50
Total Volatile Content	99.50 - 99.75	99.50 - 99.75
Water	95 - 98	95 - 98
Exempt Compound Content	0	0
Coating Category	Surface Cleaner	

**NOTE:** US/Canadian Regulations allow for the use of exempt compounds for VOC calculations.

FOR REST-OF-WORLD (outside US and Canada):

RTS REGULATORY DATA:	AS IS	
	170	
	LBS./GAL	g/L
Actual VOC	0.20 Max.	25 Max.
Density	7.5 - 8.5	900 - 1020
	WT.%	VOL.%
Total Solids Content	0.25 - 0.50	0.25 - 0.50
Total Volatile Content	99.50 - 99.75	99.50 - 99.75
Water	95 - 98	95 - 98
Coating Category	Surface Cleaner	

### NOTES

If used as instructed, this product is designed to comply with the Volatile Organic Compound (VOC) Standards in Low-VOC jurisdictions, for Automobile Refinish Coatings. Confirm compliance with state and local air quality rules before use. The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.