



## SAFETY DATA SHEET

Revision date 29-Jan-2016

Version 1

### Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name** CPS2035 Series Mixed Colors  
**Product Code** CPS2035SERIES  
**UN/ID no** UN1263  
**Recommended Use** Paint, Coatings

#### Details of the supplier of the safety data sheet

*See section 16 for more information*

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440

Valspar Industries, Inc.  
1915 Second St. W.  
Cornwall, Ontario K6H 5R6

**E-mail address** [msds@valspar.com](mailto:msds@valspar.com)

**Emergency telephone number** 1-888-345-5732

### Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

#### HAZARD STATEMENTS

Flammable liquid and vapor.  
Causes skin irritation Causes serious eye damage

#### WHMIS Hazard Class

B2 - Flammable liquid  
D2B - Toxic materials



Signal word

**DANGER**

#### PREVENTION

Keep container tightly closed Wear protective gloves/protective clothing/eye protection/face protection Use only non-sparking tools  
Take precautionary measures against static discharge Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Wash face, hands and any exposed skin thoroughly after handling

**Product Code CPS2035SERIES**

Page 1 / 10

WPNA - CANADA WHMIS SDS

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower Wash contaminated clothing before reuse If skin irritation occurs: Get medical advice/attention

**Inhalation**

IF INHALED: Call a POISON CENTER or doctor if you feel unwell

**Ingestion**

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Do NOT induce vomiting

**Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**STORAGE**

Store in a well-ventilated place. Keep cool

**DISPOSAL**

Dispose of contents/containers in accordance with local regulations

This document represents the broadest array of ingredient composition, hazard, and precautionary information for coatings produced from specified components of this Valspar product series and mixed according to Valspar instructions. The information presented in this SDS may overstate the actual ingredients contained in and the hazards and precautionary warnings recommended for the particular coating for which it is provided.

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Limestone	1317-65-3	17 - 22
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	16 - 19
Titanium dioxide	13463-67-7	0 - 14
Talc	14807-96-6	10 - 25
Barium sulfate	7727-43-7	0 - 11
n-Butyl acetate	123-86-4	5 - 8
Methyl n-amyl ketone	110-43-0	6 - 8
C.I. Pigment Blue 15	147-14-8	0 - 3
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> )	1309-37-1	0 - 2
Iron hydroxide oxide	20344-49-4	0 - 2
1-Butanol	71-36-3	1 - 3
Carbon black	1333-86-4	0 - 0.8

### Section 4: FIRST AID MEASURES

**First Aid Measures****General advice**

Get medical advice/attention if you feel unwell.

**Eye contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

**Skin Contact**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower Wash contaminated clothing before reuse If skin irritation occurs: Get medical advice/attention

**Inhalation**

IF INHALED: Call a POISON CENTER or doctor if you feel unwell

**Ingestion**

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Do NOT induce vomiting

**Most important symptoms and effects, both acute and delayed**

**Symptoms** No information available.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

**Section 5: FIRE FIGHTING MEASURES**

**Flammable properties** Flammable liquid.

**flash point** 9 °F / -13 °C

**Upper flammability limit:** No information available

**Lower flammability limit:** No information available

**Autoignition temperature** No information available

**Explosion data**

Sensitivity to Mechanical Impact No information available.

Sensitivity to Static Discharge No information available.

**Suitable extinguishing media**

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**Specific hazards arising from the chemical**

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes.

**Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

**Section 6: ACCIDENTAL RELEASE MEASURES**

**Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

**Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

**Methods for containment**

Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.

## Section 7: HANDLING AND STORAGE

### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

### General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

### Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines

#### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	Alberta	British Columbia	Ontario TWA	Quebec	OSHA PEL
Limestone 1317-65-3		TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup> STEL: 20 mg/m <sup>3</sup>		TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup> F TWA: 2.5 mg/m <sup>3</sup> dust
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust
Talc 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit
Barium sulfate 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 713 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 150 ppm STEL: 200 ppm	TWA: 150 ppm TWA: 713 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>
Methyl n-amyl ketone 110-43-0	TWA: 50 ppm	TWA: 50 ppm TWA: 233 mg/m <sup>3</sup>	TWA: 50 ppm	TWA: 25 ppm TWA: 115 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 233 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
C.I. Pigment Blue 15 147-14-8	TWA: 1 mg/m <sup>3</sup> Cu dust and mist					
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> ) 1309-37-1	TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction
Iron hydroxide oxide 20344-49-4	TWA: 1 mg/m <sup>3</sup> Fe	TWA: 1 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> STEL: 2 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	TWA: 1.0 mg/m <sup>3</sup>	

1-Butanol 71-36-3	TWA: 20 ppm	TWA: 20 ppm TWA: 60 mg/m <sup>3</sup>	TWA: 15 ppm Ceiling: 30 ppm	TWA: 20 ppm	Ceiling: 50 ppm Ceiling: 152 mg/m <sup>3</sup> S*	TWA: 100 ppm TWA: 300 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>

### Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

### Personal Protective Equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection

#### Thermal Protection

No information available

### Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid
<b>Appearance</b>	No information available
<b>Odor</b>	Solvent
<b>Color</b>	No information available
<b>Odor Threshold</b>	No information available
<b>pH value</b>	No information available
<b>Melting point/freezing point</b>	No information available
<b>Boiling point / boiling range</b>	118 °C / 244 °F
<b>flash point</b>	-13 °C / 9 °F
<b>evaporation rate</b>	No information available
<b>Flammability (solid, gas)</b>	No information available
<b>Flammability Limit in Air</b>	
<b>Upper flammability limit:</b>	No information available
<b>Lower flammability limit:</b>	No information available
<b>Vapor Pressure</b>	No information available
<b>vapor density</b>	No information available
<b>Density (lbs per US gallon)</b>	13.16
<b>specific gravity</b>	1.58
<b>Solubility(ies)</b>	No information available
<b>Partition coefficient</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Dynamic viscosity</b>	No information available

### Other information

## Section 10: STABILITY AND REACTIVITY

<b>Stability</b>	Stable under normal conditions.
<b>Incompatible materials</b>	Strong oxidizing agents. Acids. Strong reducing agents. Alkali. Combustible material.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Hazardous Decomposition Products</b>	Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ). Nitrogen oxides (NO <sub>x</sub> ). Oxides of sulfur. Chlorine.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous polymerization</b>	None under normal processing.

## Section 11: TOXICOLOGICAL INFORMATION

### Information on toxicological effects

### Information on likely routes of exposure

#### **Eye contact**

Causes serious eye damage

#### **Skin Contact**

Causes skin irritation

#### **Ingestion**

Not applicable

#### **Inhalation**

Not applicable

### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	-	-	-
Benzene, 1-chloro-4-(trifluoromethyl)-	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
Titanium dioxide	> 10000 mg/kg ( Rat )	-	-
Talc	-	-	-
Barium sulfate	-	-	-
n-Butyl acetate	= 14.13 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Methyl n-amyl ketone	= 1600 mg/kg ( Rat )	= 12.6 mL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
C.I. Pigment Blue 15	-	-	-
Iron oxide (Fe <sub>2</sub> O <sub>3</sub> )	> 10000 mg/kg ( Rat )	-	-
Iron hydroxide oxide	> 10000 mg/kg ( Rat )	-	-
1-Butanol	= 700 mg/kg ( Rat )	= 3402 mg/kg ( Rabbit )	> 8000 ppm ( Rat ) 4 h
Carbon black	-	-	-

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Skin corrosion/irritation</b>	Causes skin irritation
<b>Serious eye damage/eye irritation</b>	Causes serious eye damage
<b>Skin sensitization</b>	Not applicable
<b>Respiratory sensitization</b>	Not applicable
<b>Germ cell mutagenicity</b>	Not applicable
<b>Carcinogenicity</b>	Not applicable
<b>Reproductive Toxicity</b>	Not applicable
<b>Specific target organ toxicity (single exposure)</b>	Not applicable
<b>Specific target organ toxicity (repeated exposure)</b>	Not applicable
<b>Aspiration hazard</b>	Not applicable

**Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials. According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B		X
Carbon black	A3	Group 2B		X

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A3 - Animal Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 2B - Possibly Carcinogenic to Humans

**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**

X - Present

**Section 12: ECOLOGICAL INFORMATION**

**Ecotoxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Marine pollutant                                      This material meets the definition of a marine pollutant

Environmental precautions                      Prevent product from entering drains.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Limestone	-	-	-
Benzene, 1-chloro-4-(trifluoromethyl)-	-	-	= 3.68 mg/L Daphnia magna 48h EC50
Titanium dioxide	-	-	-
Talc	-	> 100 g/L Brachydanio rerio 96h LC50	-
Barium sulfate	-	-	-
n-Butyl acetate	= 674.7 mg/L Desmodesmus subspicatus 72 h EC50	= 100 mg/L Lepomis macrochirus 96h LC50 17 - 19 mg/L Pimephales promelas 96h LC50	-
Methyl n-amyl ketone	-	126 - 137 mg/L Pimephales promelas 96h LC50	-
C.I. Pigment Blue 15	-	-	-
Iron oxide (Fe2O3)	-	-	-
Iron hydroxide oxide	-	-	-
1-Butanol	> 500 mg/L Desmodesmus subspicatus 72 h EC50 > 500 mg/L Desmodesmus subspicatus 96 h EC50	= 1740 mg/L Pimephales promelas 96h LC50 100000 - 500000 µg/L Lepomis macrochirus 96h LC50 = 1910000 µg/L Pimephales promelas 96h LC50 1730 - 1910 mg/L Pimephales promelas 96h LC50	= 1983 mg/L Daphnia magna 48h EC50 1897 - 2072 mg/L Daphnia magna 48h EC50
Carbon black	-	-	-

**Persistence and degradability**                      No information available.

**Bioaccumulation**                                      No information available.

**Mobility**    No information available.

Chemical Name	Partition Coefficient (n-octanol/water)
Limestone	-

Benzene, 1-chloro-4-(trifluoromethyl)-	3.7
Titanium dioxide	-
Talc	-
Barium sulfate	-
n-Butyl acetate	1.81
Methyl n-amyl ketone	1.98
C.I. Pigment Blue 15	6.6
Iron oxide (Fe2O3)	-
Iron hydroxide oxide	-
1-Butanol	0.785
Carbon black	-

### Section 13: DISPOSAL CONSIDERATIONS

**Waste from residues/unused products** Disposal should be in accordance with applicable regional, national and local laws and regulations

**Contaminated packaging** Improper disposal or reuse of this container may be dangerous and illegal.

### Section 14: TRANSPORT INFORMATION

	<u>TDG</u>	<u>IMDG</u>	<u>IATA</u>
UN/ID no	UN1263	UN1263	UN1263
Proper shipping name	Paint	Paint	Paint
Hazard Class	3	3	3
Packing Group	II	II	II
Environmental hazard	Yes		
Marine pollutant	This material meets the definition of a marine pollutant		
Marine pollutant	Trizinc diphosphate , Zinc oxide		
Special Provisions		163 EmS-No F-E, S-E	A3, A72
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			No information available

### Section 15: REGULATORY INFORMATION

#### International Inventories

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory All components are listed or exempt from listing

**DSL** - Canadian Domestic Substances List All components are listed or exempt from listing

**This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR**

#### **WHMIS Hazard Class**

B2 - Flammable liquid  
D2B - Toxic materials



Chemical Name	Canada - 2013 NPRI (National Pollutant Release Inventory)
Benzene, 1-chloro-4-(trifluoromethyl)-	Part 4 Substance
n-Butyl acetate	Part 5, Individual Substances
Methyl n-amyl ketone	Part 4 Substance
C.I. Pigment Blue 15	Part 1, Group A Substance
1-Butanol	Part 1, Group A Substance

**Product Code CPS2035SERIES**

Page 8 / 10  
WPNA - CANADA WHMIS SDS



## GHS - Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Flammable liquids	Category 2

## Label elements



Signal word

**DANGER**

### **HAZARD STATEMENTS**

Highly flammable liquid and vapor  
Causes skin irritation  
Causes serious eye irritation

### **PREVENTION**

Wash face, hands and any exposed skin thoroughly after handling. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection.

### **RESPONSE**

Get medical advice/attention if you feel unwell.

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### **Skin**

If skin irritation occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

#### **Inhalation**

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

#### **Ingestion**

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

#### **Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

### **STORAGE**

Store in a well-ventilated place. Keep cool.

### **DISPOSAL**

Dispose of contents/containers in accordance with local regulations.

### **HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)**

Not applicable.

### **OTHER HAZARDS**

Not applicable.

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

## **Section 16: OTHER INFORMATION**

**Product Code CPS2035SERIES**

Page 9 / 10

WPNA - CANADA WHMIS SDS

**HMIS****Health hazards** 2

\* = Chronic Health Hazard

**Flammability** 3**Physical hazards** 0**Personal Protection** X**Supplier Address**Valspar Coatings  
701 Shiloh Rd.  
Garland, TX 75042  
972-276-5181**Prepared By** Product Stewardship**Revision date** 29-Jan-2016**Revision Note** No information available**Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**