



## SAFETY DATA SHEET

Revision date 29-Jan-2016

Version 1

### Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**Product identifier**

**Product Code** LIC40SERIES

**Product Name** LIC40 Series Mixed Colors

**Other means of identification**

No information available

**Recommended use of the chemical and restrictions on use**

Paint, Coatings

**Details of the supplier of the safety data sheet**

*See section 16 for more information*

The Valspar Corporation  
PO Box 1461  
Minneapolis, MN 55440

**E-mail address** [msds@valspar.com](mailto:msds@valspar.com)

**Emergency telephone number**

United States of America 1-888-345-5732

American Samoa, Guam, Northern Mariana Islands, Puerto Rico, U.S. Virgin Islands 1-800-255-3924

### Section 2: HAZARDS IDENTIFICATION

**Classification**

Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

**Label elements**

**Product Code LIC40SERIES**

Page 1 / 12

AGHS - USA OSHA SDS



Signal word

**DANGER**

#### **HAZARD STATEMENTS**

Flammable liquid and vapor  
May cause an allergic skin reaction  
May cause cancer  
May cause drowsiness or dizziness

#### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

##### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### **Skin**

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

##### **Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

##### **Ingestion**

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

##### **Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

#### **STORAGE**

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

#### **DISPOSAL**

Dispose of contents/containers in accordance with local regulations.

#### **HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)**

Not applicable.

#### **OTHER HAZARDS**

Causes mild skin irritation. Harmful to aquatic life with long lasting effects.

#### **UNKNOWN ACUTE TOXICITY**

0% of the mixture consists of ingredient(s) of unknown toxicity.

This document represents the broadest array of ingredient composition, hazard, and precautionary information for coatings produced from specified components of this Valspar product series and mixed according to Valspar instructions. The information presented in this SDS may overstate the actual ingredients contained in and the hazards and precautionary warnings recommended for the particular coating for which it is provided.

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Titanium dioxide	13463-67-7	0 - 35
n-Butyl acetate	123-86-4	8 - 18
Ethylene glycol monobutyl ether acetate	112-07-2	2 - 6
Carbon black	1333-86-4	0 - 8
Manganese dioxide	1313-13-9	0 - 3
Solvent naphtha, petroleum, light aromatic	64742-95-6	0 - 0.1
Xylenes	1330-20-7	0.2 - 3
Benzene, 1,2,4-trimethyl-	95-63-6	0 - 0.6
Proprietary additive	Proprietary	0.3 - 1
Proprietary additive	Proprietary	0.3 - 1
Proprietary additive	Proprietary	0.3 - 1
Ethylbenzene	100-41-4	0 - 0.5
Quartz	14808-60-7	0 - 0.4
Alkanoate ester	Proprietary	0.1 - 0.3

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### Section 4: FIRST AID MEASURES

#### First Aid Measures

##### **General advice**

IF exposed or concerned: Get medical advice/attention.

##### **Eye contact**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### **Skin Contact**

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

##### **Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

##### **Ingestion**

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

#### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

#### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

### Section 5: FIRE FIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

#### Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

### **Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## **Section 6: ACCIDENTAL RELEASE MEASURES**

### **Personal precautions, protective equipment and emergency procedures**

#### **Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

#### **For emergency responders**

Use personal protection recommended in Section 8.

### **Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

### **Methods and material for containment and cleaning up**

#### **Methods for containment**

Prevent further leakage or spillage if safe to do so.

#### **Methods for cleaning up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

## **Section 7: HANDLING AND STORAGE**

### **Precautions for safe handling**

#### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

#### **General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

### **Conditions for safe storage, including any incompatibilities**

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

#### **Incompatible materials**

None known.

## **Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Control parameters

### Exposure Limits

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Ethylene glycol monobutyl ether acetate 112-07-2	TWA: 20 ppm		TWA: 5 ppm TWA: 33 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Manganese dioxide 1313-13-9	TWA: 0.02 mg/m <sup>3</sup> Mn TWA: 0.1 mg/m <sup>3</sup> Mn	Ceiling: 5 mg/m <sup>3</sup> Mn	IDLH: 500 mg/m <sup>3</sup> Mn TWA: 1 mg/m <sup>3</sup> Mn STEL: 3 mg/m <sup>3</sup> Mn
Xylenes 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	
Benzene, 1,2,4-trimethyl- 95-63-6	TWA: 25 ppm		TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	TWA: (30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA total dust TWA: (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction TWA: (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

## Appropriate engineering controls

### Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

Tight sealing safety goggles.

### Skin and body protection

Wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber. Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing.

### Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Thermal Protection**  
No information available

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical state</b>	liquid
<b>Appearance</b>	No information available
<b>Odor</b>	Solvent
<b>Color</b>	No information available
<b>Odor Threshold</b>	No information available
<b>pH value</b>	No information available
<b>Melting point/freezing point</b>	No information available
<b>Boiling point / boiling range</b>	56 °C / 133 °F
<b>flash point</b>	27 °C / 81 °F
<b>evaporation rate</b>	No information available
<b>Flammability (solid, gas)</b>	No information available
<b>Flammability Limit in Air</b>	
<b>Upper flammability limit:</b>	No information available
<b>Lower flammability limit:</b>	No information available
<b>Vapor Pressure</b>	No information available
<b>vapor density</b>	No information available
<b>Density (lbs per US gallon)</b>	10.16
<b>specific gravity</b>	1.22
<b>Solubility(ies)</b>	No information available
<b>Partition coefficient</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Dynamic viscosity</b>	No information available

### Other information

## Section 10: STABILITY AND REACTIVITY

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous polymerization</b>	None under normal processing.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Incompatible materials</b>	None known.
<b>Hazardous Decomposition Products</b>	Carbon monoxide. Carbon dioxide (CO2).

## Section 11: TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

**Eye contact**  
Not applicable  
**Skin Contact**  
Not applicable  
**Ingestion**  
Not applicable

**Inhalation**

Not applicable

**Numerical measures of toxicity - Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
n-Butyl acetate 123-86-4	= 14.13 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Ethylene glycol monobutyl ether acetate 112-07-2	= 1600 mg/kg ( Rat )	= 1480 mg/kg ( Rabbit )	-
Carbon black 1333-86-4	-	-	-
Manganese dioxide 1313-13-9	= 9000 mg/kg ( Rat )	-	-
Solvent naphtha, petroleum, light aromatic 64742-95-6	-	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
Xylenes 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
Benzene, 1,2,4-trimethyl- 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
Proprietary additive	-	-	-
Proprietary additive	= 2615 mg/kg ( Rat )	-	-
Proprietary additive	-	-	-
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
Quartz 14808-60-7	= 500 mg/kg ( Rat )	-	-
Alkanoate ester	-	-	-

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	19538 Mg/kg
ATEmix (dermal)	10466 Mg/kg
ATEmix (inhalation-dust/mist)	10.5 mg/l
ATEmix (inhalation-vapor)	94 mg/l

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials. According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7		Group 2B		X
Ethylene glycol monobutyl ether acetate 112-07-2	A3			
Carbon black 1333-86-4	A3	Group 2B		X
Ethylbenzene 100-41-4	A3	Group 2B		X
Quartz 14808-60-7	A2	Group 1	Known	X

Product Code LIC40SERIES

Page 7 / 12

AGHS - USA OSHA SDS

**ACGIH (American Conference of Governmental Industrial Hygienists)**  
A2 - Suspected Human Carcinogen. A3 - Animal Carcinogen.  
**IARC (International Agency for Research on Cancer)**  
Group 1 - Carcinogenic to Humans. Group 2B - Possibly Carcinogenic to Humans.  
**NTP (National Toxicology Program)**  
Known - Known Carcinogen.  
**OSHA (Occupational Safety and Health Administration of the US Department of Labor)**  
X - Present.

<b>Skin corrosion/irritation</b>	Not applicable
<b>Serious eye damage/eye irritation</b>	Not applicable
<b>Skin sensitization</b>	Not applicable
<b>Respiratory sensitization</b>	Not applicable
<b>Germ cell mutagenicity</b>	Not applicable
<b>Carcinogenicity</b>	Not applicable
<b>Reproductive Toxicity</b>	Not applicable
<b>Specific target organ toxicity (single exposure)</b>	Not applicable
<b>Specific target organ toxicity (repeated exposure)</b>	Not applicable
<b>Aspiration hazard</b>	Not applicable

**Section 12: ECOLOGICAL INFORMATION**

**Ecotoxicity**

Harmful to aquatic life with long lasting effects.

Environmental precautions                      Prevent product from entering drains.

**Persistence and degradability**

No information available

**Bioaccumulation**

No information available

**Mobility**

No information available

**Other adverse effects**

No information available

**Section 13: DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes**                                      Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging**                              Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

**Section 14: TRANSPORT INFORMATION**

	<b><u>DOT</u></b>	<b><u>IMDG</u></b>	<b><u>IATA</u></b>
<b>14.1 UN/ID no</b>	UN1263	UN1263	UN1263
<b>14.2 Proper shipping name</b>	Paint related material	Paint related material	Paint related material
<b>14.3 Hazard Class</b>	3	3	3
<b>14.4 Packing Group</b>	III	III	III
<b>14.5 Environmental hazard</b>	Not applicable		
<b>14.6 Special Provisions</b>	B1, B52, IB3, T2, TP1, TP29	163, 223, 955	A3, A72
	<b>Emergency Response Guide Number</b>	<b>EmS-No</b>	
	128	F-E, S-E	



**Section 15: REGULATORY INFORMATION**

**International Inventories**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing.

**US Federal Regulations**

Chemical Name	TSCA - Toxic Substances Control Act, Section 12(b) Export Notification
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	Section 4

Chemical Name	SARA 313 - Threshold Values %	Hazardous air pollutants (HAPs) content
Raw umber 12713-03-0 0 - 15	1	Present
Ethylene glycol monobutyl ether acetate 112-07-2 2 - 6	1	Present
Manganese dioxide 1313-13-9 0 - 3	1	Present
Xylenes 1330-20-7 0.2 - 3	1	Present
Benzene, 1,2,4-trimethyl- 95-63-6 0.3 - 0.9	1	
Ethylbenzene 100-41-4 0 - 0.5	0.1	Present

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate 123-86-4	5000 lb			X
Xylenes 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**US State Regulations**

**Rule 66 status of product**

Photochemically reactive.

**California Proposition 65**

WARNING! This product contains a chemical known in the State of California to cause cancer.

**U.S. EPA Label information**

**EPA Pesticide registration number** Not applicable

**U.S. State Right-to-Know Regulations**

Chemical Name
n-Butyl acetate 123-86-4
Xylenes 1330-20-7
Titanium dioxide 13463-67-7
Toluene 108-88-3
Trade Secret
Trade Secret
Methyl acetate 79-20-9
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Iron oxide (Fe2O3) 1309-37-1
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Ethylbenzene 100-41-4
Trade Secret
Trade Secret
Aluminum 7429-90-5
Acetone 67-64-1
Trade Secret
C.I. Pigment Green 7 1328-53-6
C.I. Pigment Green 36 14302-13-7

Methyl n-amyl ketone 110-43-0
Solvent naphtha, petroleum, light aromatic 64742-95-6
Trade Secret
C.I. Pigment Blue 15 147-14-8
Trade Secret
m-Xylene 108-38-3
Trade Secret
Naphtha, petroleum, hydrotreated heavy 64742-48-9
2-Pentanone, 4-methyl- 108-10-1
Trade Secret
Trade Secret
Trade Secret
Trade Secret
Benzene, 1,2,4-trimethyl- 95-63-6
Carbon black 1333-86-4
o-Xylene 95-47-6
p-Xylene 106-42-3
Barium sulfate 7727-43-7
C.I. Pigment Yellow 129 15680-42-9
Stoddard solvent 8052-41-3
2-Butanone, oxime 96-29-7
Quartz 14808-60-7

## Section 16: OTHER INFORMATION

### **HMIS**

**Health hazards** 2\*

\* = Chronic Health Hazard

**Flammability** 3

**Physical hazards** 0

**Personal Protection** X

### **Supplier Address**

Valspar Coatings  
701 Shiloh Rd.  
Garland, TX 75042  
972-276-5181

**Prepared By** Product Stewardship

**Product Code LIC40SERIES**

Page 11 / 12  
AGHS - USA OSHA SDS

Revision date 29-Jan-2016  
Revision Note No information available

**Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. **UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

**End of Safety Data Sheet**